

# HOG 500

## 1024 CHANNEL CONTROLLER FOR MOVING AND CONVENTIONAL LIGHTS



### DESCRIPTION

The HOG 500 console is a lighting control console designed to handle any combination of lighting fixtures, moving or static, with moving lights as simple to programme as conventional luminaires. With flexible programming and playback options the HOG 500 is well suited to a wide variety of applications, making it the ideal choice for the control of both simple and complex dimming systems as well as colour scrollers and moving lights.

### FEATURES

- Controls up to 1024 channels
- Configuration of the desk makes programming easy
- LCDs provide continuous feedback on programming and playback status together with cue or palette lists
- Instant access to console features
- Automenu and advanced fixture control
- All shows are stored on standard 3.5 inch DOS format floppy disks
- Cues, cue lists, effects and presets can be merged from one show to another
- Split fade times on any parameter
- Easy to understand command line syntax
- External VGA monitor output
- Cue list, cue contents, programmer, patch and actual stage output available at VDU port
- Any fixture can be patched anywhere on the DMX output
- User-definable system default settings
- Multiple fixture types simultaneously supported
- Console self-test and diagnostic routines
- Access protection PIN
- Mouse/trackball input provides pan and tilt information for selected fixtures or cursor control (mouse not supplied)
- User definable fixture libraries
- Wholehog II® operating system
- Show data transferable from/to Wholehog II, Echelon II and HOG1000, and from Jands Hog 600/500/250 consoles (some restrictions apply)



### OVERALL SPECIFICATIONS


Control channels:	1024
Submasters:	8
Memory:	2.0 Mbytes (expandable to 4.0 Mbytes)
Power supply:	Universal 100 - 240 VAC ±10%, 47 - 63 Hz
Consumption:	45W typical
Connector:	IEC 3-pin with integral fuse, switch and mains filter
Fuse:	2A M205/240V
DMX out:	2 x USITT DMX-512/1990 protocol (RS-485 standard) / AXR 5-pin female socket
VDU out:	High density 15-pin D connector (for VGA monitor)
MIDI in/thru/out:	3 x 5-pin 180° DIN socket
Desk lamp out:	1 x 12V current limited, dimmable, AXR 3-pin female socket (10W total maximum consumption)
Keyboard input:	5-pin 180° DIN socket
Mouse/trackball input:	9-pin male D connector
Displays:	Programmer section: One 320 x 240 pixel graphics LCD, white backlight Playback section: One 40 character x 2 line LCD, white backlight
Disk drive:	High density DOS compatible 3.5 inch disk drive
Dimensions:	700mm(W) x 400mm(D) x 140mm(H)
Net/shipping weight:	12/18 kg

### SUPPLIED ACCESSORIES

- 2m IEC to Clipsal 463 power cable (export models may vary)
- Floppy disk with operating software/fixture libraries
- Operating manual

### ORDERING INFORMATION

MODEL/PART	PART NUMBER
HOG 500 console	JND-HOG500
Desk lamps	CAE-18XR/CAE-18XR-Hi
Flightcase	JND-FC-HOG500



1024 CHANNEL CONTROLLER FOR MOVING AND CONVENTIONAL LIGHTS

# HOG 500

# HOG 500

## 1024 CHANNEL CONTROLLER FOR MOVING AND CONVENTIONAL LIGHTS



### ARCHITECT & ENGINEERS SPECIFICATIONS

#### Electronics

The lighting control console shall provide control of up to 1024 control channels via the industry standard USITT DMX-512/1990 protocol. The DMX output sockets on the back panel shall be 5-pin AXR. The output voltages shall conform to standard RS-485 balanced serial data transmission.

The console shall have a VGA video output for connection to an external VDU. The connector shall be a high density 15-pin D connector.

The console shall have MIDI In, MIDI Thru, and MIDI Out connections, the sockets being standard MIDI 5-pin DIN connectors. The console shall have a keyboard socket for connection to an external PC AT-type keyboard. The connector shall be a standard 5-pin DIN connector.

The console shall have eight (8) playback master faders to individually play back cue lists.

The console shall have a programmer with numeric keypad and function buttons to create 'looks' on stage by selecting fixtures and parameters. Three (3) wheels shall be utilised to select and set various parameters.

The console shall utilise two (2) liquid crystal displays (LCDs) to provide feedback to the operator.

The console shall have a floppy disk drive to store or transfer show information on standard high density DOS format 3.5 inch disks. The console shall have a memory capacity of at least 2.0 Mbytes and shall be battery-backed to prevent memory loss when switched off. The battery shall have a life of at least four (4) years.

The console shall incorporate design techniques and electronic filters to comply with Australian and European Union directives on electrical safety and electromagnetic compatibility (EMC).

The console shall be factory tested and cyclically burned-in for a minimum of 24 hours.

#### Operation

The console operating software shall incorporate diagnostic test routines that exercise the different systems on the CPU card. These test routines shall indicate to the operator (using LEDs and/or displays) the result (pass/fail) of the tests.

The console shall display an error message to the operator should the software malfunction or be corrupted.

#### Electrical

The console shall operate from a single-phase supply of 100-240 VAC  $\pm 10\%$ , with a supply frequency of 47 Hz to 63 Hz.

The console shall not draw more than 50 watts of power from a normal GPO. The power inlet shall be a switched and filtered IEC mains socket with integral fuse, and shall be located on the back panel of the console.

The console power supply shall be a universal-type switched mode supply requiring no changing of internal links to accommodate different supply voltages within the specified range.

#### Mechanical

The lighting control console shall be designed to be free-standing.


The console shall be 700mm wide x 400mm deep x 140mm high.

The chassis shall be constructed of 1.2mm steel, and shall be provided with a removable steel base for access to internal electronics. All metal surfaces shall be properly treated and finished in zinc or nickel plating, or powdercoat.

The control surfaces shall be scratch-resistant 0.25mm Lexan with legends reverse silk-screen printed from behind. All operator controls and displays shall be provided on the top operating surface of the console.

The chassis shall have sufficient ventilation holes to allow adequate convection cooling of the power supply, provided the ambient temperature does not exceed 40°C (104°F).

The lighting control console shall be the HOG 500.



1024 CHANNEL CONTROLLER FOR MOVING AND CONVENTIONAL LIGHTS

# HOG 500